



RCW10 & RCW12

- New 10" and 12" subwoofers

Reference series RCW10 & RCW12. The first DLS natural RAW bass powerful subwoofers.
 Dual 4 ohm voice coils to get the max out of your amp.
 Heavy duty push terminals for long size speaker wires.
 Parameters optimized for both vented and sealed boxes.
 Resonance damping rubber coated steel basket.

Aluminium "one cone body" for extensive bass control.
 Overseed rubber surround for stabel high excision.



Specifications

	RCW 10 CS-RCW10	RCW12 CS-RCW12
Art.number	CS-RCW10	CS-RCW12
Size	25 cm (10")	30 cm (12")
Impedance	2 x 4 ohm	2 x 4 ohm
Power handling, RMS	300 Watts	400 Watts
Power handling, max / peak	600 / 800 Watts	800 / 1000 Watts
Freq. range	25 Hz - 1 kHz	20 Hz - 1 kHz
Cone material	Aluminum "One cone body"	
Weight	5,3 kg	9,5 kg
Re	2 x 3,2 ohm	2 x 3,2 ohm
X-max	+9 mm (0,35")	+9 mm (0,35")
Installation depth	133 mm	155 mm
Mounting hole	235 mm	284 mm
Outer diameter	266 mm	315 mm
Magnet diameter	160 mm	188 mm
Sensitivity	84,4 dB	86,5
Fs	28,2 Hz	29,7 Hz
Vas	37,6 litres	48,6 litres
Qts	0,37	0,38
Rec. sealed box	18 litres	28 litres
Rec. vented box	20 litres / 3" port 34 cm	33 litres/ 4" port 52 cm
* All parameters measured with voice coils connected in parallel.		