



# Marine NEWS



The DLS Marine series expands with a new waterprotected amplifier that are the result of DLS continued strive to supply the best sound available. Exquisitely sound tuned in England and with the extra power expected by a demanding audience - still at an affordable price.

Class A/B balanced sound with both details and raw power. Advanced noise rejecting high level input for direct connection to factory radios. Auto start on high level input and oversized power and speaker cable terminals. High and Low pass filters & +6 dB dynamic bass EQ

Powerful and small amplifier with power output 4 x 150 Watts, and in mono bridge connection it puts out 2 x 200 Watts.

Including side panels in silicone for extra waterprotection.

Number of channels	4	Filter high-pass variable	50 - 500 Hz*
Amplifier class	AB	Filter low pass variable	50 - 500 Hz *
Power output, RMS 4 ohm/THD	4 x 70 W /0,1%	* can be switched in/out	
Power output, RMS 2 ohm/THD	4 x 100 W /0,2%	Bass EQ @ 50 Hz	+ 6dB
Peak music power, RMS 2 ohm	4 x 150 W	Power consumption, idle	0,5 A
Power output, RMS 4 ohm bridged/THD	2 x 200 W /1%	Power consumption, max	50A
Signal to noise ratio, A-weighted	>95 dB	Fuse	2 x 25 A
Damping factor	>80	Dimensions HxWxD(mm)	55 x 188 x 320
Frequency response	10 Hz - 30 kHz	Dimensions (inch)	2,16 x 7,44 x 12,67
Input impedance, low level	22 kohm	Weight	3 kg
Input sensitivity	0,25 - 5V	Art,Number	CA-M40
Input impedance, high level	47 ohm		
High level input	Yes		